

# COMP26020 Programming Languages and Paradigms Part 1: C Programming

---

## Memory Safety

```
└─$ ./basic-test-suite
basic-test-suite.c:344:allocate:PASS
basic-test-suite.c:347:init_rand:PASS
basic-test-suite.c:348:init_zeros:PASS
basic-test-suite.c:349:init_identity:PASS
basic-test-suite.c:352:equal:PASS
basic-test-suite.c:355:sum:PASS
basic-test-suite.c:356:scalar_product:PASS
basic-test-suite.c:357:transposition:PASS
basic-test-suite.c:358:product:PASS
basic-test-suite.c:363:dump_file:PASS
basic-test-suite.c:366:load_from_file:PASS
basic-test-suite.c:369:dump_and_load_from_file:PASS
basic-test-suite.c:372:equal_file:PASS
basic-test-suite.c:375:sum_file:PASS
basic-test-suite.c:376:scalar_product_file:PASS
[1] 15440 segmentation fault ./basic-test-suite
└─$
```

**pierre@pop** ~/Desktop/comp26020/lab/lab1/code <master>

# Memory Unsafety in C Programs

- C, and other languages e.g. C++ **are inherently memory unsafe**
- There is absolutely no check at runtime if memory accessed is initialised, allocated, or mapped
- In most cases the compiler won't warn you either

# Memory Unsafety in C Programs

- C, and other languages e.g. C++ **are inherently memory unsafe**
- There is absolutely no check at runtime if memory accessed is initialised, allocated, or mapped
- In most cases the compiler won't warn you either
- **A few examples of memory errors:**
  - Out of bounds accesses on buffers (e.g. overflow)

# Memory Unsafety in C Programs

- C, and other languages e.g. C++ **are inherently memory unsafe**
- There is absolutely no check at runtime if memory accessed is initialised, allocated, or mapped
- In most cases the compiler won't warn you either
- **A few examples of memory errors:**
  - Out of bounds accesses on buffers (e.g. overflow)
  - Out of bounds arrays indexing

# Memory Unsafety in C Programs

- C, and other languages e.g. C++ **are inherently memory unsafe**
- There is absolutely no check at runtime if memory accessed is initialised, allocated, or mapped
- In most cases the compiler won't warn you either
- **A few examples of memory errors:**
  - Out of bounds accesses on buffers (e.g. overflow)
  - Out of bounds arrays indexing
  - Dereferencing `NULL` or freed (*dangling*) pointers

# Memory Unsafety in C Programs

- C, and other languages e.g. C++ **are inherently memory unsafe**
- There is absolutely no check at runtime if memory accessed is initialised, allocated, or mapped
- In most cases the compiler won't warn you either
- **A few examples of memory errors:**
  - Out of bounds accesses on buffers (e.g. overflow)
  - Out of bounds arrays indexing
  - Dereferencing `NULL` or freed (*dangling*) pointers
  - Failure to initialise stack/heap-allocated variables before read access

# Memory Unsafety in C Programs

- C, and other languages e.g. C++ **are inherently memory unsafe**
- There is absolutely no check at runtime if memory accessed is initialised, allocated, or mapped
- In most cases the compiler won't warn you either
- **A few examples of memory errors:**
  - Out of bounds accesses on buffers (e.g. overflow)
  - Out of bounds arrays indexing
  - Dereferencing `NULL` or freed (*dangling*) pointers
  - Failure to initialise stack/heap-allocated variables before read access
  - Memory leaks



# Memory Unsafety in C Programs

- C, and other languages e.g. C++ **are inherently memory unsafe**
- There is absolutely no check at runtime if memory accessed is initialised, allocated, or mapped
- In most cases the compiler won't warn you either
- **A few examples of memory errors:**
  - Out of bounds accesses on buffers (e.g. overflow)
  - Out of bounds arrays indexing
  - Dereferencing `NULL` or freed (*dangling*) pointers
  - Failure to initialise stack/heap-allocated variables before read access
  - Memory leaks
  - Double free

# Memory Unsafety in C Programs

- C, and other languages e.g. C++ **are inherently memory unsafe**
- There is absolutely no check at runtime if memory accessed is initialised, allocated, or mapped
- In most cases the compiler won't warn you either
- **A few examples of memory errors:**
  - Out of bounds accesses on buffers (e.g. overflow)
  - Out of bounds arrays indexing
  - Dereferencing NULL or freed (*dangling*) pointers
  - Failure to initialise stack/heap-allocated variables before read access
  - Memory leaks
  - Double free
  - Use-after-free

# Memory Unsafety in C Programs

- C, and other languages e.g. C++ **are inherently memory unsafe**
- There is absolutely no check at runtime if memory accessed is initialised, allocated, or mapped
- In most cases the compiler won't warn you either
- **A few examples of memory errors:**
  - Out of bounds accesses on buffers (e.g. overflow)
  - Out of bounds arrays indexing
  - Dereferencing NULL or freed (*dangling*) pointers
  - Failure to initialise stack/heap-allocated variables before read access
  - Memory leaks
  - Double free
  - Use-after-free
  - etc.

# Memory Unsafety in C Programs

- Memory errors are **hard to detect, hard to debug**
  - No warning/error at compile-time
  - Undefined behaviour: at runtime sometimes it crashes, sometimes not...

# Memory Unsafety in C Programs

- Memory errors are **hard to detect, hard to debug**
  - No warning/error at compile-time
  - Undefined behaviour: at runtime sometimes it crashes, sometimes not...

 **These bugs have huge security implications!** 

Exploiting these bugs an attacker can:

- Leak sensitive data (e.g. passwords, crypto keys)
- Tamper with sensitive data
- Escalate privileges
- Take over the entire program

# Microsoft: 70 percent of all security bugs are memory safety issues

Percentage of memory safety issues has been hovering at 70 percent for the past 12 years.

By Catalin Cimpanu for Zero Day | February 11, 2019 | Topic: Security




Image: Matt Miller

## Chrome: 70% of all security bugs are memory safety issues

Google software engineers are looking into ways of eliminating memory management-related bugs from Chrome.

By Catalin Cimpanu for Zero Day | May 23, 2020 | Topic: Security




Image: Google

RELATED

- Apple: Side-loading on iOS would open the malware floodgates  
Security
- Work to earn several highly respected CompTIA certifications with these self-paced courses  
Security
- US indicts UK resident 'PlugwalkJoe' for cryptocurrency theft  
Security

NEWSLETTERS

**ZDNet Security**  
Your weekly update on security around the globe, featuring research, threats, and more.

Sources: <https://zd.net/3q8axgo>, <https://zd.net/3wfFHU7>

# Example 1: Infoleak

# Example 1: Infoleak

Assume the following scenario:

- A security-sensitive program is distributed in binary-only form
- It contains sensitive data: a password
- An attacker has access to the binary only and aims to figure out the password



# Example 1: Infoleak

Original code:

```
char *welcome_message = "Hi there! How is it going?\n"; // 27 char
char *password = "secret";
char entered_password[128];

int main(int argc, char **argv) {
    for(int i=0; i<27; i++) // Print welcome message character by character
        printf("%c", welcome_message[i]);

    printf("Please input the password:\n");
    scanf("%s", entered_password);

    if(!strcmp(entered_password, password)) { printf("Passowrd ok!\n"); /* ... */ }
    else { printf("Wrong password! aborting\n"); }

    return 0;
}
```

[23-memory-safety/infoleak-orig.c](https://23-memory-safety.infoleak-orig.c) 

# Example 1: Infoleak

Updated code (welcome\_message shortened):

```
char *welcome_message = "Hi there!\n"; // shortened welcome message, only 11 chars now
char *password = "secret";
char entered_password[128];

int main(int argc, char **argv) {
    for(int i=0; i<27; i++)
        printf("%c", welcome_message[i]);

    printf("Please input the password:\n");
    scanf("%s", entered_password);

    if(!strcmp(entered_password, password)) { printf("Passowrd ok!\n"); /* ... */ }
    else { printf("Wrong password! aborting\n"); }

    return 0;
}
```

[23-memory-safety/infoleak-updated.c](#) 

# Example 1: Infoleak

Updated code (welcome\_message shortened):

```
char *welcome_message = "Hi there!\n"; // shortened welcome message, only 11 chars now
char *password = "secret";
char entered_password[128];

int main(int argc, char **argv) {
    for(int i=0; i<27; i++) // Oopsie! forgot to update that bit of the code
        printf("%c", welcome_message[i]);

    printf("Please input the password:\n");
    scanf("%s", entered_password);

    if(!strcmp(entered_password, password)) { printf("Passowrd ok!\n"); /* ... */ }
    else { printf("Wrong password! aborting\n"); }

    return 0;
}
```

[23-memory-safety/infoleak-updated.c](#) 

# Example 1: Infoleak

Updated code (welcome\_message shortened):

```
char *welcome_message = "Hi there!\n"; // shortened welcome message, only 11 chars now
char *password = "secret";
char entered_password[128];

int main(int argc, char **argv) {
    for(int i=0; i<27; i++) // Oopsie! forgot to update that bit of the code
        printf("%c", welcome_message[i]);

    printf("Please input the password:\n");
    scanf("%s", entered_password);

    if(!strcmp(entered_password, password)) { printf("Passowrd ok!\n"); /* ... */ }
    else { printf("Wrong password! aborting\n"); }

    return 0;
}
```

[23-memory-safety/infoleak-updated.c](https://github.com/0x00sec/23-memory-safety/infoleak-updated.c)



# Example 1: Infoleak

Updated code (welcome\_message shortened):

```
char *welcome_message = "Hi there!\n"; // shortened welcome message, only 11 chars now
char *password = "secret";
char entered_password[128];

int main(int argc, char **argv) {
    for(int i=0; i<27; i++) // Oopsie! forgot to update that bit of the code
        printf("%c", welcome_message[i]);

    printf("Please input the password:\n");
    scanf("%s", entered_password);

    if(!strcmp(entered_password, password)) { printf("Passowrd ok!\n"); /* ... */ }
    else { printf("Wrong password! aborting\n"); }

    return 0;
}
```

[23-memory-safety/infoleak-updated.c](#)



# Example 1: Infoleak

Updated code (welcome\_message shortened):

```
char *welcome_message = "Hi there!\n"; // shortened welcome message, only 11 chars now
char *password = "secret";
char entered_password[128];


int main(int argc, char **argv) {
    for(int i=0; i<27; i++) // Oopsie! forgot to update that bit of the code
        printf("%c", welcome_message[i]);

    printf("Please input the password:\n");
    scanf("%s", entered_password);

    if(!strcmp(entered_password, password)) { printf("Passowrd ok!\n"); /* ... */ }
    else { printf("Wrong password! aborting\n"); }

    return 0;
}
```

[23-memory-safety/infoleak-updated.c](#)



## Example 2: Sensitive Data Tampering

# Example 2: Sensitive Data Tampering

Assume the following scenario:

- Same type of program performing a password check
- This time we assume that the attacker has access to the source code (e.g. open source program)
- For that reason the password is stored encrypted
- Attacker aims to bypass the password check



# Example 2: Sensitive Data Tampering

```
char user_input[32] = "0000000000";
char password_hash[32] = "tfdsfu"; // "secret" encrypted with caesar cypher with shift 1

int main(int argc, char **argv) {
    if(argc != 2) { printf("Usage: %s <password>\n", argv[0]); return 0; }

    strcpy(user_input, argv[1]);
    caesar_encrypt(user_input);

    if(!strcmp(password_hash, user_input, strlen(password_hash))) {
        printf("login success!\n");
        /* do important stuff ... */
    } else { printf("wrong password!\n"); }

    return 0;
}
```

[23-memory-safety/tampering.c](https://github.com/23-memory-safety/tampering.c) 

# Example 2: Sensitive Data Tampering

```
char user_input[32] = "0000000000";
char password_hash[32] = "tfdsfu"; // "secret" encrypted with caesar cypher with shift 1

int main(int argc, char **argv) {
    if(argc != 2) { printf("Usage: %s <password>\n", argv[0]); return 0; }

    strcpy(user_input, argv[1]);
    caesar_encrypt(user_input);

    if(!strcmp(password_hash, user_input, strlen(password_hash))) {
        printf("login success!\n");
        /* do important stuff ... */
    } else { printf("wrong password!\n"); }

    return 0;
}
```

[23-memory-safety/tampering.c](#) 



# Example 2: Sensitive Data Tampering

```
char user_input[32] = "0000000000";
char password_hash[32] = "tfdsfu"; // "secret" encrypted with caesar cypher with shift 1


int main(int argc, char **argv) {
    if(argc != 2) { printf("Usage: %s <password>\n", argv[0]); return 0; }

    strcpy(user_input, argv[1]);
    caesar_encrypt(user_input);

    if(!strcmp(password_hash, user_input, strlen(password_hash))) {
        printf("login success!\n");
        /* do important stuff ... */
    } else { printf("wrong password!\n"); }

    return 0;
}
```

[23-memory-safety/tampering.c](https://github.com/23-memory-safety/tampering.c) 



# Example 2: Sensitive Data Tampering

```
char user_input[32] = "0000000000";
char password_hash[32] = "tfdsfu"; // "secret" encrypted with caesar cypher with shift 1


int main(int argc, char **argv) {
    if(argc != 2) { printf("Usage: %s <password>\n", argv[0]); return 0; }

    strcpy(user_input, argv[1]);
    caesar_encrypt(user_input);

    if(!strcmp(password_hash, user_input, strlen(password_hash))) {
        printf("login success!\n");
        /* do important stuff ... */
    } else { printf("wrong password!\n"); }

    return 0;
}
```

[23-memory-safety/tampering.c](https://github.com/23-memory-safety/tampering.c) 



# Example 2: Sensitive Data Tampering

```
char user_input[32] = "0000000000";
char password_hash[32] = "tfdsfu"; // "secret" encrypted with caesar cypher with shift 1


int main(int argc, char **argv) {
    if(argc != 2) { printf("Usage: %s <password>\n", argv[0]); return 0; }

    strcpy(user_input, argv[1]);
    caesar_encrypt(user_input);

    if(!strcmp(password_hash, user_input, strlen(password_hash))) {
        printf("login success!\n");
        /* do important stuff ... */
    } else { printf("wrong password!\n"); }

    return 0;
}
```

[23-memory-safety/tampering.c](https://github.com/23-memory-safety/tampering.c) 



## Example 3: Stack Smashing

# Example 3: Stack Smashing

- Classic control flow hijacking attack:
  - Attacker has external (e.g. command line) access to the program
  - Attacker exploits a bug to make the program execute code it's not supposed to
- Originally proposed in 1996 here:  
<http://www.phrack.org/archives/issues/49/14.txt>
- First let's see how the CPU manage function calls/returns

# Example 3: Stack Smashing


## C CODE

```
int f(double param)
{
    /* ... */
    g(x);
    /* ... */
}


void g(int param) {
    /* ... */
    return;
}
```




# Example 3: Stack Smashing




# Example 3: Stack Smashing



# Example 3: Stack Smashing



# Example 3: Stack Smashing



# Example 3: Stack Smashing

```
char *password = "upqtfdsfu"; // properly encrypted password

void security_critical_function() { printf("launching nukes!!\n"); }

void preprocess_input(char *string) {
    char local_buffer[16];
    strcpy(local_buffer, string);
    /* work on local buffer ... */
    return;
}

int main(int argc, char **argv) {
    if (argc != 2) { printf("usage: %s <password>\n", argv[0]); return -1; }

    preprocess_input(argv[1]);
    caesar_encrypt(argv[1]);

    if(!strcmp(password, argv[1], strlen(password)))
        security_critical_function();
    else printf("Unauthorised user!\n");

    return 0;
}
```

[23-memory-safety/stack-smashing.c](#) 

# Example 3: Stack Smashing

```
char *password = "upqtfdsfu";

void security_critical_function() {
    printf("launching nukes!!\n");
}

void preprocess_input(char *string) {
    char local_buffer[16];
    strcpy(local_buffer, string);
    /* work on local buffer ... */
}

int main(int argc, char **argv) {
    if (argc != 2) { /* ... */ }

    preprocess_input(argv[1]);
    caesar_encrypt(argv[1]);

    if(!strcmp(password, argv[1],
                strlen(password)))
        security_critical_function();
    else printf("Unauthorised user!\n");
    return 0;
}
```

[23-memory-safety/stack-smashing.c](#) 

# Example 3: Stack Smashing

```
char *password = "upqtfdsfu";

void security_critical_function() {
    printf("launching nukes!!\n");
}


void preprocess_input(char *string) {
    char local_buffer[16];
    strcpy(local_buffer, string);
    /* work on local buffer ... */
}

int main(int argc, char **argv) {
    if (argc != 2) { /* ... */ }

    preprocess_input(argv[1]);
    caesar_encrypt(argv[1]);

    if(!strcmp(password, argv[1],
                strlen(password)))
        security_critical_function();
    else printf("Unauthorised user!\n");
    return 0;
}
```

[23-memory-safety/stack-smashing.c](https://github.com/PierreOlivier23/memory-safety/stack-smashing.c)



Stack layout in memory when `preprocess_input` runs

# Example 3: Stack Smashing

```
char *password = "upqtfdsfu";

void security_critical_function() {
    printf("launching nukes!!\n");
}


void preprocess_input(char *string) {
    char local_buffer[16];
    strcpy(local_buffer, string);
    /* work on local buffer ... */
}

int main(int argc, char **argv) {
    if (argc != 2) { /* ... */ }

    preprocess_input(argv[1]);
    caesar_encrypt(argv[1]);

    if(!strcmp(password, argv[1],
                strlen(password)))
        security_critical_function();
    else printf("Unauthorised user!\n");
    return 0;
}
```

[23-memory-safety/stack-smashing.c](https://github.com/0x00sec/23-memory-safety/stack-smashing.c)





# Example 3: Stack Smashing

```
char *password = "upqtfdsfu";

void security_critical_function() {
    printf("launching nukes!!\n");
}


void preprocess_input(char *string) {
    char local_buffer[16];
    strcpy(local_buffer, string);
    /* work on local buffer ... */
}

int main(int argc, char **argv) {
    if (argc != 2) { /* ... */ }

    preprocess_input(argv[1]);
    caesar_encrypt(argv[1]);

    if(!strcmp(password, argv[1],
                strlen(password)))
        security_critical_function();
    else printf("Unauthorised user!\n");
    return 0;
}
```

[23-memory-safety/stack-smashing.c](#)



# Example 3: Stack Smashing

```
char *password = "upqtfdsfu";

void security_critical_function() {
    printf("launching nukes!!\n");
}


void preprocess_input(char *string) {
    char local_buffer[16];
    strcpy(local_buffer, string);
    /* work on local buffer ... */
}

int main(int argc, char **argv) {
    if (argc != 2) { /* ... */ }

    preprocess_input(argv[1]);
    caesar_encrypt(argv[1]);

    if(!strcmp(password, argv[1],
                strlen(password)))
        security_critical_function();
    else printf("Unauthorised user!\n");
    return 0;
}
```

[23-memory-safety/stack-smashing.c](#)



# Example 3: Stack Smashing

```
char *password = "upqtfdsfu";

void security_critical_function() {
    printf("launching nukes!!\n");
}


void preprocess_input(char *string) {
    char local_buffer[16];
    strcpy(local_buffer, string);
    /* work on local buffer ... */
}

int main(int argc, char **argv) {
    if (argc != 2) { /* ... */ }

    preprocess_input(argv[1]);
    caesar_encrypt(argv[1]);

    if(!strcmp(password, argv[1],
                strlen(password)))
        security_critical_function();
    else printf("Unauthorised user!\n");
    return 0;
}
```

[23-memory-safety/stack-smashing.c](#)



## Example 4: Use-After-Free

# Example 4: Use-After-Free

```
typedef struct {
    double member1; double member2;
    void (*member3)(int);
} my_struct;

void print_hello(int x) {
    printf("Hello, parameter: %d\n", x);
}

void security_critical_function() {
    printf("Launching nukes!\n");
    /* ... */
}

//
```

```
int main(int argc, char **argv) {
    /* allocate and init ms */
    my_struct *ms = malloc(sizeof(my_struct));
    ms->member1 = 42.0; ms->member2 = 42.0;
    ms->member3 = &print_hello;
    /* call the function pointer */
    ms->member3(12);

    free(ms);
    char *buffer = malloc(12);
    strcpy(buffer, argv[1]);

    ms->member3(12);
    /* check a password, runs sec_crit_fn */
}
```

[23-memory-safety/stack-smashing.c](https://23-memory-safety/stack-smashing.c) 

# Example 4: Use-After-Free

```
typedef struct {  
    double member1; double member2;  
    void (*member3)(int);  
} my_struct;  
  
void print_hello(int x) {  
    printf("Hello, parameter: %d\n", x);  
}  
  
void security_critical_function() {  
    printf("Launching nukes!\n");  
    /* ... */  
}  
  
//
```

```
int main(int argc, char **argv) {  
    /* allocate and init ms */  
    my_struct *ms = malloc(sizeof(my_struct));  
    ms->member1 = 42.0; ms->member2 = 42.0;  
    ms->member3 = &print_hello;  
    /* call the function pointer */  
    ms->member3(12);  
  
    free(ms);  
    char *buffer = malloc(12);  
    strcpy(buffer, argv[1]);  
  
    ms->member3(12);  
    exit(0);  
}
```


[23-memory-safety/stack-smashing.c](https://23-memory-safety/stack-smashing.c) 


- `member3` is a **function pointer**
  - Can be dynamically set and called at runtime

# Example 4: Use-After-Free

```
typedef struct {  
    double member1; double member2;  
    void (*member3)(int);  
} my_struct;  
  
void print_hello(int x) {  
    printf("Hello, parameter: %d\n", x);  
}  
  
void security_critical_function() {  
    printf("Launching nukes!\n");  
    /* ... */  
}  
  
//
```

```
int main(int argc, char **argv) {  
    /* allocate and init ms */  
    my_struct *ms = malloc(sizeof(my_struct));  
    ms->member1 = 42.0; ms->member2 = 42.0;  
    ms->member3 = &print_hello;  
    /* call the function pointer */  
    ms->member3(12);  
  
    free(ms);  
    char *buffer = malloc(12);  
    strcpy(buffer, argv[1]);  
  
    ms->member3(12);  
    /* check a password, runs sec_crit_fn */  
}
```

[23-memory-safety/stack-smashing.c](https://23-memory-safety/stack-smashing.c) 




# Example 4: Use-After-Free

```
typedef struct {  
    double member1; double member2;  
    void (*member3)(int);  
} my_struct;  
  
void print_hello(int x) {  
    printf("Hello, parameter: %d\n", x);  
}  
  
void security_critical_function() {  
    printf("Launching nukes!\n");  
    /* ... */  
}  
  
//
```

```
int main(int argc, char **argv) {  
    /* allocate and init ms */  
    my_struct *ms = malloc(sizeof(my_struct));  
    ms->member1 = 42.0; ms->member2 = 42.0;  
    ms->member3 = &print_hello;  
    /* call the function pointer */  
    ms->member3(12);  
  
    free(ms);  
    char *buffer = malloc(12);  
    strcpy(buffer, argv[1]);  
  
    ms->member3(12);  
    /* check a password, runs sec_crit_fn */  
}
```

[23-memory-safety/stack-smashing.c](https://23-memory-safety/stack-smashing.c)






# Example 4: Use-After-Free

```
typedef struct {  
    double member1; double member2;  
    void (*member3)(int);  
} my_struct;  
  
void print_hello(int x) {  
    printf("Hello, parameter: %d\n", x);  
}  
  
void security_critical_function() {  
    printf("Launching nukes!\n");  
    /* ... */  
}  
  
//
```

```
int main(int argc, char **argv) {  
    /* allocate and init ms */  
    my_struct *ms = malloc(sizeof(my_struct));  
    ms->member1 = 42.0; ms->member2 = 42.0;  
    ms->member3 = &print_hello;  
    /* call the function pointer */  
    ms->member3(12);  
  
    free(ms);  
    char *buffer = malloc(12);  
    strcpy(buffer, argv[1]);  
  
    ms->member3(12);  
    /* check a password, runs sec_crit_fn */  
}
```

[23-memory-safety/stack-smashing.c](https://23-memory-safety/stack-smashing.c)




# Example 4: Use-After-Free

```
typedef struct {  
    double member1; double member2;  
    void (*member3)(int);  
} my_struct;  
  
void print_hello(int x) {  
    printf("Hello, parameter: %d\n", x);  
}  
  
void security_critical_function() {  
    printf("Launching nukes!\n");  
    /* ... */  
}  
  
//
```

```
int main(int argc, char **argv) {  
    /* allocate and init ms */  
    my_struct *ms = malloc(sizeof(my_struct));  
    ms->member1 = 42.0; ms->member2 = 42.0;  
    ms->member3 = &print_hello;  
    /* call the function pointer */  
    ms->member3(12);  
  
    free(ms);  
    char *buffer = malloc(12);  
    strcpy(buffer, argv[1]);  
  
    ms->member3(12);  
    /* check a password, runs sec_crit_fn */  
}
```

[23-memory-safety/stack-smashing.c](https://23-memory-safety/stack-smashing.c)



# Summary

- C is **not memory safe**
  - Memory issues benign at a first glance can have **huge security consequences**
  - How to avoid these?
- 

Feedback form: <https://bit.ly/3iybv0Y>

